

	HWg-STE	HWg-STE plus	Poseidon 3266	Poseidon2 3266	Poseidon 3268	Poseidon2 3268	Poseidon 3468	Poseidon2 3468	Poseidon 4002	Poseidon2 4002
SNMP v1	+	+	+	+	+	+	+	+	+	+
SNMP v2/3				Q2 2014		Q2 2014		Q2 2014		Q2 2014
SNMP Trap			+	+	+	+	+	+	+	+
Trap destinations	0	0	2	5	2	5	2	5	2	5
SNTP	+	+	+	+	+	+	+	+	+	+
SMTP	+	+	+	+	+	+	+	+	+	+
SMTP TLS				+		+		+		+
SSL				+		+		+		+
SMS/ local								+		+
SMS/ netGSM			+	+	+	+	+	+	+	+
SMS destinations	0	0	2	5	2	5	2	5	2	5
Logger				+		+		+		+
Log records	0	0	0	250,000	0	250,000	0	250,000	0	250,000
HWg-Push		+		+		+		+		+
Comm monitor				+		+		+	+	+
1-Wire	2	2	5	8	5	8	4	8	12	16
1-Wire UNI				+		+		+	+	+
RS-485 sensors										+
Modbus /TCP			+	+		+	+	+	+	+
Alarm reminder				+		+		+	+	+
Periodical Status				+		+		+	+	+
VLAN				+		+		+		+
Inputs (DI)	0	2	4	4	4	4	4	4	8	12
Outputs (DO)	0	0	0	0	2	2	2 (230V)	2 (230V)	2	4
Operating temp.	0-65°C	0-65°C	0-65°C	-35-85°C	0-65°C	-35-85°C	0-65°C	-35-85°C	0-65°C	-35-85°C